



Note.

- Two lengths of PC pin are available to give a 12.5 or 15 mm centre to the board.
- 10 mm pin centres are standard but 7.5 mm is also available.

SPINDLE VARIATIONS *		BUSH VARIATIONS †		
Type	X (mm)	Y (mm)	W (mm)	Type
Plastic or Metal Fixed	4	M7 x 0.75	6	CG
Plastic or Metal Fixed	4	M7 x 0.75	6	CEP
Plastic or Metal Fixed	4	M10 x 0.75	8	CP
Plastic Fixed	6	M10 x 0.75	8	CP

Flatted spindles are available.

*See P16 Potentiometer 'SPINDLE DATA' leaflets for more information.

† See P16 Potentiometer 'BUSH DATA' leaflet for more information.

Mechanical and Electrical Specification - see separate leaflet.

TO ORDER see over.

This information is supplied in good faith but the customer is politely reminded that it is their responsibility to check the suitability of our products for their particular application. Please note that all dimensions are for reference purposes only and, as it is the Company's policy to continuously improve our products, we reserve the right to incorporate changes without notice.

Omeg Ltd.
Imberhorne Industrial Estate
East Grinstead
West Sussex RH19 1RJ
ENGLAND

Tel. +44 (0) 1342 410420 Fax. +44 (0) 1342 316253
E-mail omeg.sales@omeg.co.uk
<http://www.omeg.co.uk>